

DUVILAX® KL-40

Properties

Homopolymeric polyvinyl acetate dispersion in the aqueous environment containing plasticiser and inorganic filler. The emulsion system consists of a non-ionic emulsifier and polyvinyl alcohol as a protective colloid. It is biodegradable.

Application

Duvilax KL-40 is a special dispersive adhesive intended for the production of paper honeycombs (cores of honeycomb boards) and industrial glueing in the paper industry.

Packaging

plastic packages: 30kg keg, 125kg barrel; 200kg, 220kg steel barrel; plastic container 1,000kg; rail and road tanker.

Parameters

appearance	viscous liquid of white colour
dry matter content	min. 39,0%
viscosity	1 000 – 4 000 mPa.s (Rheotest) 2 000 – 10 000 mPa.s (Brookfield RVT, ISO 2555)
pH	6 – 8
film properties	white, slightly elastic, soft and non-sticky

Storage

Duvilax KL-40 is stored in the original, undamaged and closed containers, at the temperature ranging from 5°C to 40°C; it must not be exposed to direct sunlight. Goods delivered in cisterns are stored in specially designed reservoirs protected against corrosion due to the effect of the slightly acid environment. Free access of air from the surrounding environment needs to be prevented in reservoirs (for example via a water valve) or reservoirs need to be equipped with an agitator. Avoid mixing with other agents and micro-biologically defective material. After emptying a reservoir, the reservoir needs to be cleaned and disinfected with a biocidal agent.

Warranty

6 months from the date of production if storage conditions are observed.

Updated: 05/2017

This technical data sheet cancels all previous versions and replaces them. Information contained therein are not binding and are only of an informative and general character. They are based on our own experience, research and objective testing. The product meets the above specifications only during the warranty period and under the conditions in this data sheet. The company Duslo, Inc. does not guarantee the suitability of the product for a particular purpose. Use of the product for a specific purpose, including suitability for a particular purpose and methods of its use, is the customer obliged to test in specific technology conditions. Information relating to health and safety at work are provided in the Material Safety Data Sheet. More product information, details and contacts are available on www.duslo.sk. Written and / or oral advice, relating to a product, has the character of a non-binding recommendation.