

DUVILAX® PT-29

Properties

Homopolymeric polyvinyl acetate dispersion in the aqueous environment without fillers and plasticisers. The emulsion system consists of a non-ionic emulsifier and polyvinyl alcohol as a protective colloid. It is biodegradable.

Application

Duvilax PT-29 is a special dispersion adhesive indented for production of paper tubes, paper protective corners, solid boards, etc. In general, it is used for glueing individual layers of paper, for products at which high hardness needs to be achieved at relatively small paper thickness, at low coating of adhesive and achieving high speed of glueing. Duvilax PT-29 has an adhesive effect in wet condition, it creates a hard and strong connection after drying out the coating of adhesive. It is used without dilution or other treatments. Duvilax PT-29 may be applied for glueing materials coming into contact with food and for children's toys.

Packaging

plastic packages: 30kg keg, 125kg barrel; steel barrel 200kg, 220kg; plastic container 1,000kg; rail and car tank.

Parameters

appearance	viscous liquid of white colour
dry matter content	min. 28,0 %
viscosity	700 – 3 000 mPa.s (Brookfield RVT, ISO 2555)
pH	3,0 – 6,0
film properties	transparent, hard, fragile and non-sticky

Storage

Duvilax PT-29 is stored in the original, undamaged and closed containers, at the temperature ranging from 5°C to 40°C; it must not be exposed to direct sunlight. Goods delivered in tankers are stored in specially designed reservoirs protected against corrosion due to the effect of the slightly acid environment. Free access of air from the surrounding environment needs to be prevented in reservoirs (for example via a water valve) or reservoirs need to be equipped with an agitator. Avoid mixing with other agents and micro-biologically defective material. After emptying a reservoir, the reservoir needs to be cleaned and disinfected with a biocidal agent.

Warranty

6 months from the date of production if storage conditions are observed.

Updated: 05/2017

This technical data sheet cancels all previous versions and replaces them. Information contained therein are not binding and are only of an informative and general character. They are based on our own experience, research and objective testing. The product meets the above specifications only during the warranty period and under the conditions in this data sheet. The company Duslo, Inc. does not guarantee the suitability of the product for a particular purpose. Use of the product for a specific purpose, including suitability for a particular purpose and methods of its use, is the customer obliged to test in specific technology conditions. Information relating to health and safety at work are provided in the Material Safety Data Sheet. More product information, details and contacts are available on www.duslo.sk. Written and / or oral advice, relating to a product, has the character of a non-binding recommendation.