DUVILAX® Basic primer - penetration



Copolymer dispersion on the vinyl acetate – versatate base in the aqueous environment. The emulsion system consists of a non-ionic emulsifier and polyvinyl alcohol as a protective colloid. It is biodegradable.

Application

Duvilax Basic Penetration is a dispersion intended for impregnating unequally or excessively soaked substrates under interior coating, coat, self-levelling screed, painting, thin-film mineral and acrylate plasters, before glueing facing, floor tiling, PVC- floor covering, linoleum, etc. In addition, it is also used for reinforcing soaked surfaces and for dust-free adjustments of concrete coatings. It is suitable for the use in exteriors, interiors and for floor heating.

Packaging

plastic packages: 1kg, 5kg and 10kg, 5L can, 30kg, 125kg; steel .barrel 200kg, 220kg; 1,000kg plastic container.

Parameters

appearance	viscous liquid of white colour
dry matter content	10 ± 1 %
min. film forming temperature	5 °C
рН	4 - 6
film properties	transparent, soft and non-sticky

Storage

Stored in the original, undamaged and closed containers, at the temperature ranging from 5°C to 40°C; it must not be exposed to direct sunlight.

Warranty

The guarantee period for the product delivered in packing up to 15 kg gross is 12 months. For the rest of the packagings it is 6 months, in the case of keeping the storage conditions mentioned above.

Updated:

This technical data sheet cancels all previous versions and replaces them. Information contained therein are not binding and are only of an informative and general character. They are based on our own experience, research and objective testing. The product meets the above specifications only during the warranty period and under the conditions in this data sheet. The company Duslo, Inc. $does not \, guarantee \, the \, suitability \, of \, the \, product \, for \, a \, particular \, purpose. \, Use \, of \, the \, product \, for \, a \, specific \, purpose, \, including \, suitability \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, purpose \, and \, purpose \, purpose \, and \, purpose \, purpose$ customer obliged to test in specific technology conditions. Information relating to health and safety at work are provided in the Material Safety Data Sheet. More product information, details and contacts are available on www.duslo.sk. Written and / or oral advice, relating to a product, has the character of a non-binding recommendation.

