DUVILAX® BD-20/51



Properties

Homopolymeric polyvinyl acetate dispersion in the aqueous environment containing an external plasticiser. The emulsion system consists of a non-ionic emulsifier and polyvinyl alcohol as a protective colloid. It is biodegradable.

Application

Duvilax BD-20/51 is a special adhesive used for mechanical gluing of smooth cardboard, in production of books with thick pages used by children and for production of folding picture-books, in polygraphy for glueing of book blocks spines. It is also suitable for machine laminating of smooth or corrugated cardboard. Duvilax BD-20/51 may be applied for gluing materials coming into contact with food.

Packaging

plastic packages: 30kg keg, 125kg; steel barrel 200kg, 220kg; plastic container 1,000kg; rail and car tank.

Parameters

appearance	viscous liquid of white colour
dry matter content	min. 51,0 %
viscosity	1500 – 2 000 mPa.s (Rheotest)
рН	3 – 6
min.film forming temperature	2°C
film properties	transparent, elastic, soft and slightly sticky

Storage

Duvilax BD-20/51 is stored in the original, undamaged and closed containers, at the temperature ranging from 5°C to 40°C; it must not be exposed to direct sunlight. Goods delivered in cisterns are stored in specially designed reservoirs protected against corrosion due to the effect of the slightly acid environment. Free access of air from the surrounding environment needs to be prevented in reservoirs (for example via a water valve) or reservoirs need to be equipped with an agitator. Avoid mixing with other agents and micro-biologically defective material. After emptying a reservoir, the reservoir needs to be cleaned and disinfected with a biocidal agent.

Warranty

6 months from the date of production if storage conditions are observed.

Updated:

This technical data sheet cancels all previous versions and replaces them. Information contained therein are not binding and are only of an informative and general character. They are based on our own experience, research and objective testing. The product meets the above specifications only during the warranty period and under the conditions in this data sheet. The company Duslo, Inc. $does not \, guarantee \, the \, suitability \, of \, the \, product \, for \, a \, particular \, purpose. \, Use \, of \, the \, product \, for \, a \, specific \, purpose, \, including \, suitability \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, methods \, of \, its \, use, \, is \, the \, product \, for \, a \, particular \, purpose \, and \, purpose \, and \, purpose \, purpose \, and \, purpose \, purpose$ customer obliged to test in specific technology conditions. Information relating to health and safety at work are provided in the Material Safety Data Sheet. More product information, details and contacts are available on www.duslo.sk. Written and / or oral advice, relating to a product, has the character of a non-binding recommendation.

